

INDEX

- (n, k) cyclic code, 616
- 90° phase lag component, 345
- A , 258
- AC , 243
- B , 258
- C , 258
- $C0$, 130
- $C1$, 130
- $CC0$, 131
- $CC1$, 131
- D , 160
- $DC0$, 242
- $DC1$, 242
- $DAT1$, 581
- $DAT2$, 581
- F_s , 337
- F_t , 337
- I_{DDQ} current limit, 452
- I_{DDQ} decision threshold, 455, 456
- I_{DDQ} fault, 66
- I_{DDQ} testing, 14, 439
- I_{DDQ} testing time, 453
- I_{DDT} test, 258
- I_{defmin} , 459
- LU factorization, 396
- M , 258
- M/N , 338
- M/N synchronization, 319
- N , 258
- N_{max} , 459
- $O(n)$ complexity, 263
- P , 337
- PC , 243
- R , 342
- $SC0$, 131
- $SC1$, 131
- SO , 131
- $S_{x_i}^{T_j}$, 398
- T_s , 504
- T_j , 399
- T_{aps} , 306
- V_G , 583
- V_H , 583, 585
- V_L , 583, 585
- V_L switch, 591
- V_{TH} , 581
- ΔI_{DDQ} testing, 456
- Δ , 316, 339
- \Downarrow , 262
- \Rightarrow , 263
- \Uparrow , 262
- $\alpha 0$, 179
- $\alpha 1$, 179
- α particle, 259, 261
- $\beta 0$, 179
- $\beta 1$, 179
- β , 49
- \Downarrow , 262
- \forall , 263
- λ , 178
- μ , 178
- μ law ADC, 338
- μ law encoder, 361, 367
- \overline{D} , 160
- ϕ , 178
- ψ , 178
- $\rho_{x_i}^{T_j}$, 398
- \rightarrow , 262
- $\sin(x)/x$ distortion, 354
- $\sin(x)/x$, 320
- \uparrow , 262
- \downarrow , 262
- \rightarrow , 262
- d_{seq} , 226
- k , 258
- n , 258
- t -WSF, 536
- 0-controllability, 130
- 0-observability, 131
- OTLP, 368
- 1-controllability, 130
- 1-observability, 131
- 13-valued algebra, 433
- 2-SAT, 164
- 2-coupling fault, 268
- 3-SAT, 164
- 41-valued algebra, 434
- A law encoder, 361, 367
- A/D converter, 322, 338
- AB1, 580, 583, 591
- AB1N, 589
- AB2, 580, 583, 591
- AB2N, 589
- Abadir, 263, 627
- ABF, 258, 271
- ABM, 580, 583
- ABna, 590

- ABnb, 590
- ABnN, 589
- Abraham, 266, 396
- Abramovici, 78, 171, 206, 621
- absolute dominator, 197
- AC, 36
- AC parametric test, 30, 32
- AC voltmeter, 346
- acceptance test, 17, 48, 596
- access time test, 303
- activation cost, 243
- activation energy, 261
- active and passive neighborhood pattern, 288
- active and passive neighborhood pattern sensitive fault, 258
- active area, 476
- active gate, 103
- active neighborhood pattern, 288
- active neighborhood pattern sensitive fault, 258, 272
- activity list, 103
- ad-hoc DFT, 466
- adaptive GA, 247
- ADC, 322, 338
- address decoder, 264
- address decoder fault, 63, 258, 273
- address descrambler, 26
- address failure memory, 26
- address formatting, 306
- address generator, 530
- address set-up time sensitivity test, 303
- address stepper, 533
- Advantest Model T6682 tester, 24
- AF, 258, 273
- Agarwal, 532
- age defect, 58
- aging factor, 37
- Agrawal, P., 53, 160, 239, 502
- Agrawal, V. D., 53, 65, 129–131, 160, 239, 477, 479, 502, 621, 624, 628
- AI, 18
- air pollution, 259
- Aitken, 441, 447
- Akers, 158, 206
- alias image, 352
- aliasing, 512, 514, 518
- aliasing probability, 518
- all instructions with random data fault model, 597
- alloying, 261
- alternate assignment, 162, 174
- Ambler, 53, 627
- Amerasekera, 627
- analog ATPG, 411
- analog automatic test-pattern generation, 397
- analog backtrace, 407
- analog bipartite graph, 400, 401, 403
- analog boundary module, 580, 583
- analog circuit connectivity matrix, 399
- analog circuit design for testability, 401, 404, 413
- analog circuit element, 399
- analog circuit graph, 399
- analog circuit parameter, 399
- analog circuit performance, 399, 401
- analog component deviation, 398
- analog double-fault model, 403, 405, 406
- analog element observability, 404
- analog element tolerance, 401
- analog element tolerance box, 400, 403
- analog element variation, 399
- analog fault coverage, 398, 401
- analog fault observation, 401
- analog fault ordering, 393
- analog fault simulation, 390
- analog multiple fault model, 398
- analog output parameter, 398, 400
- analog output parameter measurement, 399
- analog reverse simulation, 407, 410
- analog signal flow graph inversion, 408
- analog single-fault model, 405
- analog switch resistance, 591
- analog switch sizing, 591
- analog test access port, 579
- analog test bus, 576
- analog test bus chaining, 579
- analog test bus switching pattern, 581
- analog testability analysis, 401
- analog tolerance computation, 398
- analog triple-fault model, 405, 406
- AND bridging fault, 61, 258, 271
- ANP, 288
- ANPSF, 258, 272, 286
- aperture uncertainty, 352
- APNP, 288
- APNPSF, 258
- appearance fault, 61, 65
- application specific integrated circuit, 8
- Arabian, 622, 628
- arbitration priority set-up time, 306
- arbitration test, 305
- architectural design, 7
- area overhead, 475, 493
- Armstrong, 109, 176
- array level, 261
- artificial intelligence, 18
- ASIC, 8
- assertion fault, 60
- asymmetric coupling fault, 270
- asynchronous clear, 230
- asynchronous loop, 233
- asynchronous preset, 230
- at-speed test, 9, 42, 490, 611
- at-speed testing, 435
- AT1, 580
- AT1N, 589
- AT2, 580
- AT2N, 589
- AT&T standard telecom test, 359

- AT&T standards, 372
- ATE, 10, 18, 22, 24
- ATE algorithmic pattern generator, 26
- ATE noise, 380
- ATE scan pattern generator, 26
- ATE sequential pattern generator, 26
- ATPG, 155
- attenuation distortion test, 373
- audio front end, 27
- auditing, 8
- autocorrelation, 343
- autocorrelation property, 504
- automatic test equipment, 10, 18, 22, 24, 364
- automatic test-pattern generation, 155
- automatic test-pattern generation computational complexity, 166
- average costs, 36
- average diagnostic length, 602
- average product, 39

- B1 cell, 583
- B2 cell, 583
- BACK algorithm, 219
- back substitution, 396
- backdriving, 492
- backtrace, 175, 219
- backtracing, 150, 187
- backtrack, 162, 174
- backup, 162
- backward implication, 173
- backward time expansion, 223
- backwards logic simulation, 163
- bad-gate, 113
- band fault simulation, 397
- band-pass case, 353
- Bardell, 506, 619, 624
- bare-board interconnect test, 21
- base cell, 272
- bathtub curve, 37
- Bayes' rule, 5
- BDD, 158
- Bearnson, 625
- bed-of-nails fixture, 491
- bed-of-nails tester, 21, 549
- Beenker, 624
- behavioral level, 60, 91, 92, 148
- behavioral level testability, 148
- behavioral model, 264
- behavioral synthesis, 148
- behavioral view, 389
- benefit-cost analysis, 35, 492
- benefit-cost ratio, 42
- benefits, 41
- Bening, 625
- Bennetts, 610, 623, 624
- Bergeron, 626
- BF, 258, 271
- Bhattacharya, 204, 625
- Bhavsar, 477
- BIC sensor, 458

- BIDIR cell, 571
- bidirectional behavior, 167
- bidirectional fault, 271
- bidirectional input, 448
- BILBO, 495, 497
- bilinear transform, 397
- binary counter, 499
- binary decision diagram, 158
- binary tree, 158
- binding, 149
- binomial coefficient, 122
- BIST, 36, 43, 489
- BIST controller, 533, 539
- BIST initialization, 527
- black-box model, 264
- Bleeker, 623
- board inductance, 551
- board level, 261
- Boltzmann voltage noise, 358
- bonding deterioration, 260
- Boolean contrapositive, 198
- Boolean difference, 161
- Boolean false expression, 165
- Boolean false function, 203
- Boolean partial derivative, 161
- Boolean polynomial, 615
- Boolean satisfiability, 164
- Bose, 424, 434
- bottom-up construction, 595
- boundary register, 553, 581
- boundary register cell, 553
- boundary scan, 43, 527
- boundary scan data inversion rules, 566
- boundary scan description language, 569
- boundary scan hold register, 565
- boundary scan propagation delay measurement, 567
- boundary scan setup and hold time measurement, 567
- boundary scan standard, 549
- boundary-scan master, 435
- branch coverage, 60, 597
- branch fault, 61
- branch-and-bound search, 166, 176
- breadboard, 83
- breadth-first search, 195
- Breuer, 238, 543, 621, 625
- Brglez, 131
- brick wall filter, 381
- bridging fault, 14, 61, 65, 178, 258, 271, 443
- bridging resistance, 444
- broad-side delay test, 431
- broadband noise, 381
- Brooks, 595
- brown noise, 381
- brown-out, 14
- Bryant, 69, 92
- BSDL, 569
- BSDL entity description, 570
- BSM2, 435

- buffer pin, 571
- built-in current sensor, 458
- built-in current testing, 458
- built-in logic block observer, 495, 497, 519
- built-in self-test, 36, 43, 466, 489
- burn-in, 20, 44
- burn-in coverage, 439
- burst mode, 318
- bus driver conflict, 552
- bus fault, 61
- bus-oriented BIST, 498
- Bushnell, 199, 406, 628
- Butler, 628
- BYPASS instruction, 564, 585
- bypass register, 553, 562, 564

- C cell, 583
- C-message filter, 373
- C-message weighting curve, 375
- CA, 511
- Ca, 581
- cache block, 298
- cache DRAM, 254, 296
- cache miss test, 298
- calculus of redundant faults, 200
- calibrate cell, 581
- calibration, 313, 590
- calibration error, 360
- Campbell, 627
- Capture-IR state, 571
- Case, 68, 78, 125
- CATAPULT, 204
- catastrophic analog fault, 387, 406
- catastrophic analog fault test, 391, 398, 399
- catastrophic fault, 314
- CCITT, 359, 372
- CDRAM, 254
- CE scaling, 14
- cell, 267
- cell coupling fault, 63
- cell row, 475
- cellular automaton, 499, 511
- center frequency, 380
- central office, 366
- CF, 258, 266, 268
- CFdyn, 258, 269, 270
- CFid, 258, 270
- CFin, 258, 269
- CFS, 238
- Chakraborty, K., 626
- Chakraborty, T. J., 432
- Chakradhar, 164, 201, 203, 628
- Chakravarty, 626
- Chang, 465, 625
- channel, 26
- channel-connected components, 93, 95
- characteristic polynomial, 505, 507, 508, 516, 519
- characterization test, 18, 375, 390, 591
- Chatterjee, 396
- Chattopadhyay, 624
- checkpoint fault, 78
- checkpoint theorem, 78
- checksum test, 300
- chemical sensor, 613
- Chen, 628
- Cheng, K.-T., 239, 479, 481, 624, 626, 628
- Cheng, W.-T., 117, 219, 221
- chip level, 261
- Ciciani, 628
- circuit element, 398
- circuit level, 91, 93
- circuit-under-test, 24, 495
- circular fault masking, 64
- circular self-test path BIST, 525
- CLAMP instruction, 562, 587
- Clarke, 85, 625
- clipping level, 325
- clock, 212
- CLOCK cell, 571
- clock divider, 320
- clock fault, 214, 231
- clock rate, 10
- clock skew, 429
- ClockDR signal, 559, 560
- closest neighbor scan wiring, 478
- clustered defects, 45
- clustering parameter, 45, 49
- CMOS stuck-open fault, 274
- Co, 581
- CO (central office), 366
- CO (combinational observability), 131
- code format, 323
- code histogram, 326
- code polynomial, 616
- code word, 616
- CODEC, 366
- CODEC test, 375
- coder-decoder, 366
- coherence, 320
- coherence requirement, 339
- coherent correlation, 342
- coherent filtering, 342
- coherent measurement, 337
- coherent multi-tone testing, 356
- coherent sampling, 339
- coherent testing, 339
- collapse ratio, 74
- column decoder, 266
- combinational 0-controllability, 131
- combinational 1-controllability, 131
- combinational fault simulation complexity, 166
- combinational loop, 233
- combinational observability, 131
- Combinational robust delay test, 433
- common-mode voltage, 592
- COMPACTEST, 206
- compaction, 513
- companion matrix, 505, 507

- comparator, 380
- compiled-code simulator, 102
- complementarity pivoting, 391, 392
- complementarity variable, 392
- complementary pivot method, 391
- complete multiple backtrace, 200
- completeness, 159
- component boundary, 451
- component level, 60
- compression, 513
- computed distortion, 376
- concurrent BIST, 530
- concurrent fault detection phase, 240
- concurrent fault simulator, 113, 238
- concurrent operation test, 298
- concurrent testing, 495
- conductance fault model, 446
- conducting path, 445
- cone segmentation, 500
- conflict, 162
- consistency procedure, 178
- constant electric-field scaling, 14
- Constructive Dilemma, 198
- CONT-2, 239
- contact test, 30
- contactor, 27
- contention circuit, 305
- contention test, 306
- CONTEST, 239
- CONTROL cell, 571
- control cell, 581
- control point, 529
- control-and-observe boundary scan cell, 565
- controllability, 129
- controllability iteration, 142
- controlling event, 423
- CONTROLR cell, 571
- convergence, 114
- converter gain, 323
- COP, 131
- core, 529, 605, 606
- core isolation, 591
- core-disconnect state, 585
- core-disconnect switch, 587
- core-test language, 607
- correlated delay defects, 435
- correlator, 343
- corrosion, 259, 260
- cosmic ray, 261
- cost, 36
- cost function, 240, 241, 402
- count function, 537
- coupled cell, 269, 270
- coupling capacitance, 592
- coupling cell, 269
- coupling fault, 256, 258, 268
- CRC, 300, 514
- CREATOR, 116
- CRIS, 247
- critical area, 283
- critical data pattern, 84
- critical path, 418
- critical path length, 283
- critical path tracing, 125, 206
- critical resistance, 444
- critical timing path, 434
- cross-correlation, 343
- cross-point, 61
- cross-point fault, 61, 65
- crossover, 247
- Crouch, 624
- CSTP, 525
- CTL, 607
- cube intersection, 177
- current noise, 380
- current testing, 14, 440
- current transmission, 591
- current vector, 240
- CUT, 24, 495
- cutoff frequency, 381
- cutting algorithm, 130
- cycle breaking, 481
- cycle-free circuit test complexity, 227
- cycle-free circuits, 225
- cyclic redundancy check code, 514
- cyclic redundancy code, 300, 615
- cyclic redundancy code test, 300
- cyclic s-graph, 229

- D cell, 583
- D flip-flop, 212
- D-ALG, 176
- D-Algorithm, 176, 180
- D-chain, 180
- D-cube, 177
- D-drive, 178
- D-frontier, 163, 174
- D-intersection, 177, 181
- D/A converter, 322
- D1, 581
- D2, 581
- DAC, 322
- DAC glitch area, 323, 352
- DAC settling time, 323
- DAG, 226, 427, 480
- Das Gupta, 483
- data flow graph, 148
- data generator, 530, 533
- data path synthesis rule SR1, 148
- data path synthesis rule SR2, 148
- data polynomial, 616
- data retention fault, 258
- data transfer test, 298
- Data1 cell, 581
- Data2 cell, 581
- David, 628
- Davis, 627
- dB, 325, 368
- DBM, 580
- dBm0, 368

- DC analog fault simulation, 391, 392
- DC bin, 350, 357
- DC offset error, 323
- DC parametric test, 30
- DC testing, 435
- DCC, 242
- de-correlator, 522
- de-glitching of DAC, 318
- decibel, 325, 368
- decision point, 178
- deductive fault simulator, 109
- deep submicron device, 613
- defect, 45, 58, 61
- defect coverage, 16
- defect density, 45
- defect frequency, 58
- defect level, 36, 47
- defect per million, 439
- defect-oriented fault, 61, 65
- defect-oriented testing, 54
- deGyvez, 627
- delay element, 295
- delay fault, 61, 418, 444
- delay fault BIST, 540
- delay fault testing, 483
- delay size, 61
- delay test, 87
- delay test with scan, 431
- delay testing, 12
- delay-fault BIST, 435
- deleted neighborhood, 272
- Demidenko, 624
- Deming, 17
- derived measurement, 381
- design debug test, 18
- design for testability, 4, 35, 466, 491, 608
- design level, 60
- design verification, 60, 83
- detection probability, 505
- Devadas, 628
- device ID register, 553
- device identification register, 563
- device specification document, 22
- device-under-test, 24
- DFG, 148
- DFT, 35, 341, 346, 348, 466, 491
- diagnosis, 6, 47, 58, 63, 89, 106, 124, 257, 489, 496
- diagnostic resolution, 489, 596, 598, 610
- diagnostic run time, 540
- diagnostic test, 390, 423, 596, 598
- diagnostic tree, 598, 600
- dielectric permeability, 12
- dielectric permittivity, 12
- difference state, 221
- differential I_{DDQ} testing, 456
- differential ATAP port, 589
- differential fault simulation, 117
- differential interconnect, 577
- differential linearity error function, 325
- differential non-linearity, 325
- differential phase, 362
- differential sensitivity, 398
- digital anti-aliasing filter, 356
- digital boundary module, 580
- digital reconstruction filter, 351
- digital signal processor, 15
- digital waveform capture memory, 27
- digitizer, 27, 591
- digitizer uncertainty, 361
- digitizing threshold, 591
- Dirac delta function, 505
- directed acyclic graph, 226, 427, 480
- directed simulation-based search approach, 246
- Director, 627
- disappearance fault, 61, 65
- discontinuous amplitude quantization function, 360
- discontinuous function, 360
- discontinuous time sampling function, 360
- discrete event simulation, 102
- discrete Fourier transform, 341, 346, 348
- distortion power, 325
- distortion power due to dynamic non-linearity, 376
- dither, 314
- divergence, 114
- divided bit-line RAM, 301
- DLE, 325
- DNL, 325
- dominance fault collapsing, 76
- dominator, 197
- DRAM, 253
- DRF, 258
- drivability, 220
- driven guard wire, 592
- DSC, 242
- DSP, 15
- DSP automatic test equipment, 346
- DSP core, 606
- DSP testing, 598
- DSP-based analog testing, 388
- dual in-line package, 549
- dual transmission line, 299
- duality property, 289
- DUT, 24
- dynamic burn-in, 44
- dynamic combinational controllability, 242
- dynamic compaction, 205
- dynamic coupling fault, 258, 269, 270
- dynamic dominator, 199
- dynamic learning, 197
- dynamic neighborhood pattern sensitive fault, 272
- dynamic offset, 357
- dynamic overload, 362
- dynamic programming, 199
- dynamic RAM, 253
- dynamic sequential controllability, 242

- dynamic testability measures, 242
- E-beam testing, 157
- E-frontier, 199
- EBT, 219
- ECAT, 186
- economic efficiency, 39
- economy, 6
- EEPROM, 254, 563
- Eichelberger, 160, 467, 477, 502, 624
- Elcherif, 391
- Eldred, 59, 155
- electrical fault, 30
- electromagnetic interference, 12, 260
- electromigration, 260
- electron beam tester, 18
- electron beam testing, 129
- electronic bed-of-nails, 491
- electronically erasable programmable ROM, 254
- electrostatic discharge protector, 583
- element coverage, 400
- element node, 399
- embedded-ATE, 10
- embedded-ATE test, 611
- EMI, 12, 260
- emulated instrument, 336
- energy function, 165
- engineering economics, 35
- enhanced-scan delay testing, 430
- enterprise, 38
- envelope delay distortion, 323
- EPRM, 254
- equivalence collapsed set, 74
- equivalence collapsing, 75
- equivalence state, 221
- equivalent fault, 599
- equivalent input noise, 380
- equivalent state hashing, 199
- erasable programmable read-only memory, 254
- error, 58, 259
- error bound, 121
- error correction and translation circuit, 186
- error detection probability, 518
- error rate statistics, 610
- error seeding, 610
- error tolerance, 316
- error vector, 507
- error-correcting code, 489
- escape probability, 16
- ESD damage, 439, 583
- ESSENTIAL, 221
- essential prime implicant, 177
- EST, 199
- Eulerian sequence, 288
- evaluation frontier, 199
- event, 103
- event digitizer, 379
- event scheduling, 103
- event-driven simulator, 103
- ex situ testing, 501
- excess quantization distortion, 372
- exclusive-or operator, 617
- exhaustive pattern generator, 519
- exhaustive test generation, 160
- exhaustive testing, 495, 499
- expert system, 18
- explicit clock model, 231
- explicit digitization, 377
- exponential number of paths, 427
- extended backtrace, 219
- extended interconnect, 577
- external exclusive-OR LFSR, 503
- external frequency interference, 358
- EXTEST instruction, 560, 567, 585
- extra cross-point, 61
- extrinsic error, 370
- fabrication, 8
- failure analysis, 457
- failure mode analysis, 8, 23, 58
- failure rate, 439
- fallout rate, 50
- false path, 426
- false-path, 436
- FAN, 192
- fanout branch, 133, 162
- fanout stem, 133, 162
- fast Fourier transform, 341, 346, 348
- fast modeling clock phase, 236
- FASTEST, 221
- fault, 48, 58, 259
- fault 1, 273
- fault 2, 273
- fault 3, 273
- fault 4, 274
- fault collapsing, 71, 74, 391
- fault cone, 172
- fault coverage, 36, 88, 204
- fault coverage estimation, 150, 505
- fault density, 49
- fault detection probability, 131, 529
- fault detection probability distribution, 506
- fault detection time-frame, 222
- fault diagnosis, 89, 596
- fault dictionary, 598
- fault distribution, 53
- fault dominance, 76
- fault dropping, 204
- fault efficiency, 204
- fault equivalence, 73
- fault equivalence set, 74
- fault excitation, 162
- fault frequency, 281, 283
- fault hierarchy, 278
- fault isolation, 596
- fault linkage, 278
- fault list, 109
- fault masking, 64, 169, 278

- fault model, 4, 59, 257
- fault propagation, 162
- fault sampling, 121, 506
- fault sensitization, 162
- fault simulator, 88
- fault tree, 600
- fault-event, 113
- fault-list, 113
- fault-parallelism, 248
- faulty column map, 257
- faulty row map, 257
- FC, 36
- FDM, 352
- feature scaling, 14
- feedback bridging fault, 61, 64
- feedback index, 235
- feedback network, 503, 504, 523
- feedback set, 235
- feedback-free circuit, 226
- FFT, 341, 346, 348
- FFT leakage, 358
- fictitious delay element, 235
- field, 495
- field reject rate, 48
- field repair, 495
- field-programmable gate array, 563
- filter settling time, 317, 337, 342, 370
- final objective, 194
- firm core, 606
- first-order partial derivative of network function, 398
- first-order sensitivity, 398
- fitness function, 247
- five-valued algebra, 159
- fixed costs, 35, 36
- fixturing setup time, 524
- flat description, 94
- flicker noise, 380
- flip-chip technology, 13
- flip-flop distance contribution, 241
- flip-flop initialization, 466
- flip-flop reset hardware, 523
- floating gate defect, 441
- floating node, 98
- floating pin technique, 452
- floating point ADC, 338
- floating state, 98
- FMA, 8, 23, 58
- FMCK, 236
- FMOSSIM, 116
- formal verification method, 85
- forward implication, 172, 189
- forward substitution, 396
- Foster, 625
- Fourier, 341
- Fourier voltmeter, 343, 345
- Fourier's first principle, 343
- Fourier's second principle, 344
- FPGA, 563
- frame processor, 26
- freak failures, 20
- Freeman, 109, 156, 238
- frequency bin, 341, 349
- frequency division multiplexing, 314, 352
- frequency leakage, 349
- frequency modulation, 353
- frequency-shift keyed signal, 320
- Friedman, 621, 625
- Frohwerk, 489, 513, 514
- FSK, 320
- FSR, 323
- Fujiwara, 65, 176, 192, 193, 621
- full channel test, 366
- full scale range, 323
- full-scan, 467
- full-scan design, 157
- functional fault, 61
- functional level, 60, 91, 92, 389
- functional model, 264
- functional test, 21, 30, 59, 78, 156, 312, 386, 389, 596, 597
- functional tests for ATE, 11
- functionally sensitizable PDF, 426
- FVM, 345
- GA population, 247
- gain error, 323
- gain tracking test, 369, 372, 375
- Galey, 78, 156
- Galois field, 504
- Gamma function, 46
- Gandhi, 3
- gate overhead, 474
- gate oxide short, 441, 444, 446, 448
- gate-delay fault, 61
- GATEST, 247
- GATTO, 247
- Gaussian probability density, 122
- generator polynomial, 616
- genetic algorithm, 246
- geometrical model, 264
- Ghosh, 628
- glitch area, 314
- glitch code, 327
- global testing problem, 172
- Gmin stepping, 393
- Goel, 158, 176, 186, 187, 205, 219
- Goessel, 625
- Goldberg, 246
- Goldstein, 130, 175
- Golomb, 489, 615, 624
- good machine signature, 513
- good-event, 113
- good-gate, 113
- GPIB, 28
- Graf, 625
- graph theory flow problem, 400
- graph transitive closure, 201
- GRASP, 203
- Gray code pattern generator, 543

- gray-box model, 264
- gross-defects, 435
- ground loop, 260
- growth fault, 61, 65
- Grumberg, 625
- guard pin, 592
- guard wire, 592
- guardbanding, 21
- Gulati, 444, 448, 449, 626

- Hachtel, 625
- half-channel test, 366, 369
- Hamida, 398, 402
- Hamiltonian sequence, 287
- Hamming distance, 252, 600, 617
- hard core, 606
- hard fault, 387
- hard-core, 465, 498
- hardware description language, 91, 569
- hardware diffractor, 512
- hardware partitioning, 501
- hardware sharing, 149
- hardware test, 59
- hardware-software co-design, 597
- Harjani, 385
- harmonic analog test, 398
- harmonic distortion test, 374
- Hawkins, 626
- Hayes, 287, 514, 625
- hazard, 540
- hazard elimination, 169
- hazard-free stuck-fault test, 69
- HDL, 91
- headline, 193
- headline objective, 194
- Healy, 622
- Henftling, 203
- heterodyning, 315, 352
- heuristic, 176
- heuristic algorithm, 176
- hierarchical decomposition, 491
- hierarchical sensitivity analysis, 399
- hierarchical test, 525
- hierarchical test generation, 206
- high impedance state, 98
- high level, 60
- high-speed operation test, 298
- high-speed reload server, 26
- high-speed undersampling, 341
- HIGHZ instruction, 563, 585, 587
- HILO, 109
- HITEC, 221, 224
- Hnatek, 623
- hold time test, 33
- Holland, 246
- Holzman, 625
- homotopy/simulation continuation, 393
- Hopfield model, 165
- Householder, 393–396
- Householder's formula, 395

- Hsiao, 247, 625
- Huang, 626
- humidity, 260
- hybrid cellular automaton, 511
- hybrid pattern generator, 540, 543
- hyperactive fault, 62
- hypergeometric probability density function, 122
- hysteresis, 326

- IBM TestBench, 248
- ICT, 491, 605
- IDCODE instruction, 562, 585
- ideal converter transfer function, 322
- ideal white noise measurement, 381
- idempotent coupling fault, 258, 270
- idle channel noise, 374
- IEEE 1149.1 standard, 549
- IEEE 1149.4 standard, 575
- IEEE 1450 standard, 607
- IEEE P1500 standard, 607
- IFA, 294
- IFA-13 and Delay test, 296
- IFA-13 test, 295, 296
- IFA-6 test, 295
- IFA-9 and Delay test, 296
- IFA-9 test, 295
- ILE, 326
- IM, 315, 323, 349, 356
- image number, 353
- immediate assignment of uniquely-determined signals, 193
- impedance matching, 578
- implication arc, 202
- implication graph, 165, 201
- implication graph AND node, 203
- implication procedure, 178
- implication stack, 173
- implicit clock model, 231
- implicit clock rate, 340
- implicit digitization, 377
- improved unique sensitization procedure, 198
- in pin, 571
- in situ testing, 501
- in-band test, 363
- in-circuit test, 21, 491, 549, 575, 605
- in-phase component, 344
- incoming inspection, 17
- incoming inspection test, 20
- incompatible cubes, 177
- incorrect component orientation, 575
- increasing returns to scale, 41
- incremental sensitivity, 398
- independent analog parameter, 404
- independent faults, 206
- indistinguishability condition, 73
- inductance, 12
- inductive fault analysis, 258, 264, 294
- inertial delay, 99
- infant mortality failures, 20

- infinitely sharp band-pass filter, 346
- information content, 339, 341
- information loss, 322, 513
- information redundancy, 259
- initial condition, 518
- initial state, 223
- initialization, 212
- initialization fault, 62, 70, 217
- initialization phase, 240
- initialization vectors, 239
- INL, 326, 364
- inout pin, 571
- INPUT cell, 571
- input leakage, 302
- input MUX, 494, 496, 512, 526
- Instruction 1, 198
- Instruction 2, 198
- instruction fault, 62, 597
- instruction register, 553, 571
- instruction register OPCODE, 571
- integer-ratio synchronization, 319
- integral linearity error function, 326
- integral non-linearity, 326
- integral non-linearity error, 364
- integrated services data network, 540
- integration interval, 337
- intellectual property, 606
- inter-gate bridge, 447
- interconnect analog test, 586
- interconnect bridging, 441
- interconnect test, 591
- interdiffusion, 260
- intermittent fault, 62, 65, 259
- intermodulation component, 356
- intermodulation distortion, 315, 323, 356, 359
- intermodulation distortion test, 374
- intermodulation product, 349, 361
- INTERNAL cell, 571
- internal exclusive-OR LFSR, 507
- internal memory state, 212
- International Telegraph and Telephone Consultative Committee, 359
- interrupt test, 305
- interval counter, 380
- INTEST instruction, 560, 588, 589
- intra-gate bridge, 447
- intrinsic error, 370
- intrinsic parameter, 315, 323
- inversion coupling fault, 258, 269
- inverted signal flow graph, 407, 412
- invertible function, 513
- ionic contamination, 261
- IP, 606
- IP core, 606
- irreducible polynomial, 495, 616
- irreducible tones, 356
- irredundant test, 263
- ISDN, 540
- isolation transistor, 585
- Iyengar, 61
- Jacobian matrix, 393
- Jain, 131, 534
- Jalote, 625
- JEDEC, 562
- Jha, 69, 148, 625
- jitter, 315
- jitter noise, 376
- jitter testing, 299
- jitter-induced sampling error, 358
- Johnson, 625
- Johnson counter pattern generator, 543
- Joint Electron Device Engineering Council, 562
- Joint Test Action Group, 549
- JTAG, 549
- JTAG bi-directional pin, 565
- JTAG boundary scan, 496
- k-coupling fault, 269, 272
- Kaminska, 206, 398, 402, 622
- Khare, 627
- Kime, 602, 610
- Kinoshita, 239, 536, 537
- KMS algorithm, 437
- Kohavi, 621
- Koren, 625
- Krstić, 624
- ks/s, 315
- Kundu, 625
- Kunz, 200, 626
- Kurshan, 626
- Lala, 625
- latch-up, 459
- lattice, 261
- law of diminishing returns, 40
- layout optimization, 434
- leaf-macro, 610
- leakage, 591
- leakage current, 302
- leakage fault, 444, 446, 448
- leakage fault table, 450
- leakage test, 302
- learning procedure, 197
- Lee, C. Y., 158
- Lee, M. T. C., 626
- legacy core, 606
- level numbering, 180
- level order, 132, 135
- level ordering algorithm, 136
- level-sensitive scan design, 50, 477, 524, 528
- levelization, 102
- levelization procedure, 226
- Levi, 439
- LFSR, 300, 495, 498, 503
- LFSR cycle length, 505
- LFSR up/down counter, 531, 534
- LFSR with all-zero pattern, 530
- lightening arrester, 15
- Lin, 391, 422

- Lin-Reddy algebra, 424
- Lindbloom, 624
- line, 267
- line delay test, 428
- line justification, 162
- line-delay fault, 61, 62
- linear analog fault simulation, 395
- linear depreciation, 38, 54
- linear feedback shift register, 300, 495, 498, 503, 519
- linear phase shifter, 512
- linear quantization error, 364
- linear system, 516
- linkage pin, 571
- linked fault, 278
- Linn, 626
- logic analyzer software, 28
- logic cone, 160
- logic design, 7
- logic error, 259
- logic level, 91, 92, 132, 148
- logic transformation fault, 180
- logical fault, 63, 263
- Lombardi, 621
- long-run production, 38
- loop, 233
- loopback circuit, 527
- loopback test, 540, 581
- loss variability test, 372
- low-pass case, 353
- lowest replaceable unit, 596
- LRU, 596
- LSSD, 50, 477, 524, 528
- LTX Fusion tester, 28

- M1, 581
- M2, 581
- macro test, 609, 610
- macroeconomics, 36
- Mahoney, 309, 622
- maintenance log, 601
- maintenance test, 48
- Malaiya, 61, 446, 626
- Maly, 627
- mandatory assignment, 197
- Manning, 465, 625
- manufacturing test, 17, 59
- Mao, 444, 448, 449
- MARCH A test, 281, 285
- MARCH B test, 281, 285
- MARCH C and Delay test, 296
- MARCH C test, 281, 296, 532, 539
- MARCH C- test, 285, 304
- march element, 263
- MARCH G test, 295
- march test, 263
- MARCH X test, 285
- MARCH Y test, 285
- MARCHING 1/0 test, 281
- marginal product, 39

- Marlett, 219
- MARS hardware accelerator, 116
- mass production, 41
- master, 212
- material defect, 58
- material grains, 260
- matrix period, 504
- MATS test, 281, 285
- MATS+ and Delay test, 296
- MATS+ test, 263, 285, 296, 533, 536
- MATS++ test, 285, 304
- matured process, 46
- Maunder, 623
- maximal element tolerance, 401
- maximal length LFSR, 503
- maximum clock rate, 323
- maximum recursion depth, 201
- maximum relative variation, 403
- Maxwell, 441, 447
- Mazumder, 247, 626, 628
- McAnney, 624
- McCluskey, 54, 130, 502, 517, 528, 621
- MCM, 605
- McMillan, 626
- MDCCS, 249
- Mealy machine, 271
- mean, 360
- measured distortion, 376
- measurement, 315
- measurement error, 315, 386, 577
- measurement tolerance, 407
- measurement uncertainty, 360
- memory address scrambling, 534
- memory BIST, 529, 543
- memory cell, 258
- memory parametric testing, 301
- memory system bus burnout, 567
- memory width, 258
- MEMS, 259, 310
- MEMS part, 613
- Menon, 78, 111, 112, 621
- Mercer, 197, 204, 428, 628
- metal migration, 14
- Metze, 465, 625
- MFVS, 481
- micro electro-mechanical system, 259, 310
- micro-strip probe card, 299
- microeconomics, 35
- microprocessor clock rate, 9
- microprocessor core, 606
- microprocessor test, 10, 60, 62, 157, 158, 248, 598
- Miczo, 621
- Miller capacitance, 591
- minimal element tolerance, 401
- minimum feedback vertex set, 481
- minimum relative variation, 403
- minmax-delay simulator, 100
- misloaded component, 577
- MISR, 300, 499, 516

- MISR aliasing, 519
- missing code, 326
- missing cross-point, 61
- mixed-signal circuits, 578
- MLT, 115
- MNA, 395
- model A, 433
- model B, 433
- model C, 433
- model checking, 85
- modified nodal analysis, 395
- modular LFSR, 507
- modulo-2 arithmetic, 504, 615, 618
- Modus Ponens, 198
- Modus Tollens, 198
- monic polynomial, 509
- Monte-Carlo analysis, 265
- Monte-Carlo simulation, 397
- Moore, 12, 168
- Moore's Law, 12, 168
- MOTIS, 116
- MOZART, 116, 246
- multi-chip module, 605
- multi-domain concurrent and comparative simulation, 249
- multi-list traversal, 115
- multi-phase test point, 529
- multi-site testing, 29
- multi-tone measurement, 358
- multi-tone testing, 315, 359
- multi-valued algebra, 424
- multiple analog fault model, 402
- multiple backtrace, 194
- multiple fault, 63
- multiple fault analog test, 412
- multiple fault model, 256
- multiple parametric fault, 388
- multiple path sensitization, 162
- multiple scan register, 474
- multiple signature checking, 517
- multiple-delay simulator, 100
- multiple-input signature register, 300, 499, 516
- multiple-observation test, 218
- multiple-path fault sensitization, 159
- multiple-use drive enable signals, 565
- multiple-weight set, 510
- multiply-testable path-delay fault, 63
- multiply-testable PDF, 426
- mutation, 247
- Muth, 159, 217, 218, 245
- mutual comparator, 531, 534

- Nadeau-Dostie, 532, 606, 607, 623
- nail, 549
- Nandi, 624
- nano electronics, 613
- narrow-band tone set, 362
- near-Gaussian amplitude distribution, 362
- Needham, 624

- negative binomial probability density function, 45, 49
- negative WSF, 536
- neighborhood, 258, 272
- neighborhood pattern sensitive fault, 258, 272
- neighborhood pattern sensitive fault RAM BIST, 538
- neighborhood size, 258
- NEMESIS, 203
- netlist, 70, 84
- network transfer function, 398
- neural net ATPG, 201
- neural network, 165
- new generation, 247
- Newton, 628
- Newton's method, 412
- next state, 212
- Nicolaidis, 534, 539, 625
- nine-valued algebra, 159, 218
- noise, 315
- noise power, 381
- noise power ratio, 323
- noise referred to input, 380
- noise rejection test, 589
- noise uncertainty, 381
- nominal component value, 398
- non-Boolean primitive, 206
- non-classical fault, 64
- non-coherent sampling, 350
- non-coherent waveform, 350
- non-concurrent BIST, 530
- non-concurrent testing, 495
- non-deterministic device, 315
- non-feedback bridging fault, 61
- non-harmonic bin, 357
- non-linear distortion, 357
- non-linear distortion measurement, 357
- non-linear system, 525
- non-linearity error, 323
- non-permanent fault, 259
- non-primitive polynomial, 518
- non-robust path-delay test, 420
- non-separable code, 617
- non-static analog test, 591
- Norby, 78, 156
- normal probability density, 122
- normal system function, 498
- normalized correlation, 343
- NORTEL standards, 372
- NP-Completeness, 166
- NPR, 323
- NPSF, 258, 272
- NPSF fault detection algorithm, 290
- NPSF fault location algorithm, 290
- NS, 212
- number of equivalent bits, 364
- numerical differentiation formula, 409, 411
- Nyquist, 340
- Nyquist frequency, 352
- Nyquist frequency bin, 341

- Nyquist interval, 352
- Nyquist limit, 341, 353
- Nyquist region, 352

- OBF, 258, 271
- objective, 175, 187
- observability, 129
- observation point, 404, 529
- observe-only boundary scan cell, 564
- OBSERVE_ONLY cell, 571
- octave, 361
- off-path signal, 420
- off-set, 222
- on-path signal, 420
- on-set, 222
- one-step relaxation, 392
- ones counting, 513
- opto-electronic devices, 613
- opto-electronic interconnect, 613
- OR bridging fault, 61, 258, 271
- orthogonal tones, 356
- orthogonality, 348
- oscillation fault, 64, 108
- oscilloscope software, 28
- Osseiran, 622
- out pin, 571
- out-of-band measurement uncertainty, 363
- out-of-band test, 363
- output drive current test, 32
- output short current test, 31
- OUTPUT2 cell, 571
- OUTPUT3 cell, 571
- over-voltage power supply, 20
- oversampling filter, 352

- P/AR, 359
- package defect, 58
- package handler, 27
- package sealing, 260
- Palchadhuri, 624
- parallel BIST, 538
- parallel division synchronization, 340
- parallel fault simulator, 107
- parallel iterative simulator, 125
- parallel memory BIST, 533
- parallel shift register pattern generator, 522
- parallel value list, 125
- parallel-pattern single-fault propagation, 125, 502
- parameter node, 399
- parametric analog fault test, 399
- parametric fault, 64, 315, 387
- parametric fault test, 398
- parametric measurement unit, 27, 30
- parametric test, 11, 21
- parasitic, 58, 98, 294, 386, 442, 581
- PARIS, 125
- parity checking, 513
- parity test, 300
- Parker, 130, 238, 502, 549, 552, 575, 623
- partial hardware partitioning, 501
- partial-scan, 479
- partially detectable fault, 226
- partially testable path, 426
- partitioned test bus interface controller, 590
- partitioning, 171, 490, 595, 608
- pass/fail test, 315
- passive neighborhood pattern, 288
- passive neighborhood pattern sensitive fault, 258, 272, 287
- Patel, 204
- path classification, 428
- path count, 162
- path sensitization, 162
- path variable, 203
- path-delay fault, 61, 64, 420
- path-delay fault BIST, 542
- pattern generator, 492
- pattern matching, 26
- pattern memory, 26
- pattern multiplexing, 24
- pattern sensitive fault, 63, 65, 272
- PBX, 366
- PCB, 58, 65, 490
- PCM, 366
- PDF, 178
- PE, 26
- peak-to-average ratio test, 359
- peak-to-peak composite waveform swing, 360
- peak-to-RMS ratio, 362
- Peled, 625
- perfect test, 309
- performance overhead, 477, 493
- performance parameter, 316, 323
- periodic spectrum, 351, 352
- permanent fault, 65
- Peterson, 489, 509
- PGA, 322
- PGF, 49
- phase drift, 359
- phase lead measurement, 359
- phase meter, 346
- phase shifter, 522
- phase-locked loop, 299, 315, 319
- phone ringing frequency, 366
- physical design, 8
- physical fault, 65, 263
- PI, 12, 212
- Pilarski, 624
- pin, 26
- pin electronics, 26
- pin fault, 65
- pin multiplexing, 24, 27
- pin overhead, 493
- pin protection diode, 30
- pin solder fault, 575
- pin-permission mode, 552
- pinhole short, 441
- pink noise, 316, 381
- pipeline circuit, 226

- PLA, 61, 65, 502
- PLA fault, 65
- PLL, 299, 315, 319
- PMU, 27, 30
- PNP, 288
- PNPSF, 258, 272, 287
- PO, 212
- Poage, 156
- PODEM, 186
- pogo pin, 26
- polar output, 346
- polynomial divider, 515, 617
- polynomial modulus arithmetic, 615
- polynomial multiplier, 616
- Pomeranz, 206, 427, 428
- population size, 121
- port X/Y separation, 305
- positive WSF, 536
- potentially detectable fault, 62, 66, 112, 218
- power consumption during test, 436
- power consumption test, 31
- power density, 14
- power supply fluctuation, 260
- power-set, 201
- power-to-bandwidth ratio, 381
- power-up state, 218
- PowerMill, 479
- PPI, 135, 212
- PPO, 135, 212
- PPSFP, 125, 502
- Pradhan, 200, 625, 627
- precision measurement unit, 452
- PREDICT, 130
- PRELOAD instruction, 559, 567, 585
- present state, 212
- pressure, 260
- primary input, 12, 212
- primary output, 212
- prime tones, 356
- prime-ratio locking, 319
- primitive band, 316, 341
- primitive D-cube of failure, 178
- primitive frequency, 316, 339
- primitive frequency bin, 350
- primitive period, 341
- primitive polynomial, 300, 495, 509, 518, 619
- primitive spacing, 339
- primitive spectrum, 352
- printed circuit board, 58, 65, 490
- private branch exchange, 366
- probability density function, 123
- probability generating function, 49
- probe card, 24
- PROBE instruction, 587
- probe membrane, 24
- probe needle, 24
- probe pad, 591
- probe test, 20, 30
- process defect, 58
- process diagnosis, 8, 47
- process monitor resistor, 591
- process monitor transistor, 591
- process simulation, 46
- process yield, 44
- product quality, 35
- production, 38
- production output, 38
- production test, 19, 390
- programmable anti-aliasing filter, 322
- programmable logic array, 61, 65, 502
- programmable reconstruction filter, 320
- programmable-gain amplifier, 322
- propagation cost, 243
- propagation D-cube, 177
- propagation delay, 99, 101
- propagation delay test, 33
- propagation profile, 529
- prototyping turn, 489
- PS, 212
- pseudo LFSR, 540
- pseudo-Boolean equation, 165
- pseudo-exhaustive testing, 495, 499, 501
- pseudo-primary input, 135, 212
- pseudo-primary output, 135, 212
- pseudo-random phase distribution, 362
- pseudo-random testing, 496, 498
- pseudo-stuck-at fault, 447
- PSF, 272
- pull-up resistance, 448
- pulse code modulation, 366
- pulse modulation, 353
- pulse train matching, 26
- PVL, 125
- quadrature computation, 346
- quadrature correlator, 345
- quality, 6
- quantization bin, 358
- quantization distortion, 357, 358, 364
- quantization distortion component, 349
- quantization distortion measurement error, 363
- quantization error, 316, 364
- quantization noise, 376
- quantization power, 357
- quantization uncertainty, 381
- quantum electronics, 613
- quantum voltage, 316, 325, 326
- quiescent current, 14, 69, 440
- quiescent current monitor, 458
- QUIETEST algorithm, 451
- r, 262
- r0, 262
- r1, 262
- race, 66, 214, 233
- race fault, 66, 108, 112
- radiation, 261
- radiation coupling, 12
- radiation noise induced errors, 12

- radio frequency circuit, 613
- Rajski, 201, 506, 529, 624
- Rajsuman, 625–627
- RAM, 253
- random defects, 45
- random logic BIST, 495, 543
- random noise, 349, 357, 386
- random noise power, 376
- random pattern generation, 502
- random power, 357
- random sampling, 339
- random-access scan, 467, 484
- random-first-detection variable, 506
- random-pattern resistant fault, 512
- range of measurement uncertainty, 361
- RAS, 467, 484
- rated-clock, 9
- rated-clock delay test, 434
- read-only memory, 254
- real analog fault coverage, 404
- real event, 423
- receive filter, 355
- receive memory, 318
- reciprocal characteristic polynomial, 531
- reconstruction, 352
- reconstruction filter, 318
- reconvergent fanout, 67, 130, 132
- rectangular output, 346
- recursive learning, 200
- Reddy, 263, 422, 427, 428
- reduced coupling analog switch, 592
- reduced functional fault, 266, 267
- redundancy identification, 168
- redundant fault, 66, 70
- redundant implicant, 169
- redundant memory column, 257
- redundant memory row, 257
- reference quality voltage, 583
- reference RAM, 380
- refresh signal, 267
- Reghbati, 263, 621
- register-transfer level, 60, 92, 149
- reject rate, 453
- reject ratio, 48, 491
- relative amplitude, 363
- relative analog element deviation, 401
- relative deviation, 401
- relative prime numbers, 338
- release time test, 33
- reliability, 492
- reliability reduction, 493
- Rent's rule, 13, 609
- repair, 47
- repair using redundant cells, 21
- requirements, 7
- residue, 616
- resistive bridge, 447
- resistive short, 444
- response compacter, 492
- restricted SNPSF Test, 538
- restricted stuck-at fault, 300
- reverse pattern simulation, 205
- reverse-order simulation, 90
- RF circuit, 613
- RFD, 506
- ripple, 336
- rise and fall time test, 33
- RMS, 336, 346
- RMS function, 381
- RMS quantization uncertainty, 325
- Roberts, 622
- ROM, 254, 498
- root mean square, 336, 346
- root mean square function, 381
- root node, 158
- Ross, 78
- Roth, 78, 116, 155, 156, 159, 176, 218, 626
- routing channel, 475
- row decoder, 266
- Roychowdhury, 624
- RPG, 502
- RTI, 380
- RTL, 60, 92, 149
- Rudnick, 247, 628
- rule 150, 511
- rule 90, 511
- rule of ten, 44, 495
- RUNBIST instruction, 552, 562, 588
- running time tests, 304
- s-graph, 225, 480
- S/N ratio, 360
- s/s, 316
- SA0, 267
- SA1, 267
- Sachdev, 627
- SAF, 258, 266
- Saluja, 536, 537
- Sami, 621
- sample, 121
- sample coverage, 121
- SAMPLE instruction, 559, 567, 585
- sample set information, 377
- sample size, 121
- sampler, 27
- sampling interval, 337
- sampling jitter, 352
- sampling point, 351
- sampling rate, 337
- sampling with replacement, 121
- sampling without replacement, 121
- Samuelson, 35
- Sangiovanni-Vincentelli, 621
- Sastry, 627
- satisfiability expression, 165
- SATURN, 248
- Savir, 130, 506, 624
- SB1 switch, 583
- SB2 switch, 583
- scan chain, 522

- scan chain boundary, 448
- scan clock frequency, 479
- scan design, 43, 467
- scan flip-flop, 468
- scan flush test, 50
- scan for delay test, 431
- scan multiplexer skew, 479
- scan overhead formula, 474
- scan overheads, 474
- scan power dissipation, 479
- scan register, 467
- scan shift delay test, 431
- scan test length, 473
- scan testability rules, 469
- scan-functional delay test, 431
- scan-hold flip-flop, 483
- SCANIN, 468
- scanning electron microscope, 18
- SCANOUT, 468
- scatter, 360
- SCF, 258, 271
- schedule slippage, 489
- Schuler, 238
- Schulz, 197, 198
- SCIRTSS, 222
- SCOAP, 130
- scrambled address lines, 294
- SD switch, 583
- search space, 158
- search-space parallelism, 249
- second harmonic distortion, 356
- second-order analog transfer function, 406
- second-order harmonic, 361
- seed value, 515
- segment-delay fault, 61, 67
- selection, 247
- self-test control, 498
- Sellers, 625
- SEM, 18
- semaphore, 306
- semaphore test, 306
- SEMATECH experiment, 50, 455
- send memory, 318
- sense amplifier, 266
- sense amplifier recovery fault test, 304
- sensitivity analysis, 401
- sensitivity matrix, 399
- sensitivity-based analog test generation, 398
- sensitization value set, 236
- sensitized path segmentation, 501
- sequential 0-controllability, 131, 140
- sequential 1-controllability, 131, 140
- sequential depth, 148, 226
- sequential fault simulation complexity, 166
- sequential observability, 131, 140
- sequential robust test, 433
- sequential sampling, 125
- serial fault simulation, 106
- service interruption, 494
- Seshu, 109, 156, 238
- SEST, 221
- set-up time test, 33
- Seth, 53, 65, 69, 129–131, 505, 621
- Seth and Agrawal model, 53
- settling time, 316, 448
- SFG, 406
- SG switch, 583
- SH switch, 583
- Shannon, 353
- Shannon's expansion theorem, 161
- Shannon's sampling theorem, 353
- Sharma, 626
- Sheppard, 627
- Shi, 392–395
- shift register sequence, 489
- shift test, 471
- Shift-DR state, 562
- shift-induced bit correlation, 511
- Shmoo plot, 19, 28
- shop replaceable unit, 596
- short resistance, 446
- short-run production, 38
- shot noise, 380
- shrinkage fault, 61, 65
- SIC, 436, 542
- SIC test, 425
- signal cycle, 337
- signal flow graph, 389, 396, 406
- signal flow graph self-loop, 409
- signal information preservation, 353
- signal lag, 342
- signal lead, 343
- signal-to-distortion test, 373
- signal-to-noise ratio, 360
- signal-to-quantization noise, 319
- signal/total distortion test, 375
- signature, 489, 496, 513, 514
- signature analysis, 513
- silicon on insulator, 256
- simple interconnect, 577
- simplex method, 398, 401, 402
- Simpson, 627
- simulation, 101
- simulation level, 91
- simulation-based test generator, 214
- simulator, 83
- sinc correction, 320
- sinc distortion, 354
- sine wave generator, 27
- Singh, 628
- single cell stuck-at fault, 63
- single fault detection phase, 242
- single input change test, 425
- single parametric analog fault, 387, 401
- single stuck-at fault, 71
- single-clock scan, 471
- single-input changing pattern, 542
- single-input-change, 436
- single-tone testing, 316
- single-tone uncertainty, 363

- single-weight set, 510
- singly-testable path-delay fault, 420
- singly-untestable path, 426
- singular cover, 177
- sink node, 407
- Sivaraman, 624
- six sigma, 439
- six sigma quality, 491
- skewed-load delay test, 431
- SL switch, 583
- slave, 212
- sleeping sickness, 295
- slew limiting, 362
- SLIC, 366
- slow clock test, 11
- slow-clock delay testing, 432
- Smith, 422
- SMT, 491, 551, 605
- Snethen, 219
- SNPSF, 258, 273, 287, 536
- SOAF, 258
- SOC, 15, 386, 605, 611, 613
- SOCRATES, 197, 204
- soft core, 606
- soft fault, 387
- soft fault test, 398
- SOFTG, 219
- SOI, 256
- solder bump, 549
- Soma, 386, 622
- Somenzi, 625
- Souders, 335
- source event, 102
- source node, 407
- source stepping, 393
- spare column, 257
- spare row, 257
- sparkle code, 327
- sparse sampling, 381
- specialization, 41
- specification, 4, 6, 7
- specification testing, 389
- specification-based test, 312
- spectra, 341
- spectral component, 342
- spectral image, 354
- spectral line power, 349
- spectral mirror image, 351
- speed binning, 21
- spike suppression, 127
- SPLIT data structure, 221
- spot delay defect, 435
- SRAM, 253
- SRU, 596
- SSQ, 349, 381
- stacked capacitor, 256
- STAFAN, 125
- Stahnke, 619
- staircasing, 320
- STALLION, 222
- standard cell, 475
- standard cell library, 94
- standard deviation, 360
- standard LFSR, 503
- standard test interface language, 607
- standby current test, 305
- STAR-BIST, 512
- star-fault, 64, 66
- state coupling fault, 258, 271
- state observation, 212
- state transition graph, 222
- statement coverage, 60, 597
- static analog test, 398
- static analysis, 129
- static burn-in, 44
- static compaction, 205
- static differential linearity, 323
- static electrical discharge, 260
- static integral linearity, 323
- static learning, 197
- static neighborhood pattern sensitive fault, 258, 273, 536
- static path sensitization, 420
- static RAM, 253
- static testing, 435
- static timing analysis, 434
- statistical fault analysis, 125
- statistical sampling, 381
- statistically independent signals, 348
- statistically orthogonal signals, 348
- steady state, 14
- STEED, 222
- STG, 222
- STIL, 607
- Stoffel, 626
- STRATEGATE, 247
- stratified sampling, 125
- strobe time, 26
- Strojwas, 624, 627
- Stroud, 534
- structural analog circuit test, 406
- structural fault, 67
- structural test, 59, 78, 155, 156, 386
- structural view, 389
- structure graph, 480
- structured DFT, 467
- stuck-at fault, 65, 67, 156, 258, 267
- stuck-closed fault, 446
- stuck-on fault, 14, 68
- stuck-open address decoder fault, 258
- stuck-open fault, 67, 444
- stuck-open transistor, 448
- stuck-short fault, 67, 70
- STUMPS, 522
- sub-threshold conduction, 440, 455
- sub-threshold conduction leakage, 459
- subscriber loop, 366
- subscriber loop interface circuit, 366
- substrate coupling noise, 380
- Suk, 263

- sum of squares, 349, 381
- supergate, 130
- superlinear speed up, 41, 249
- superposition error, 326
- superposition principle, 516
- surface-mount technology, 491, 551, 605
- swept frequency measurement, 358
- switch level, 91, 92
- switching delay, 99
- switching relay, 318
- symbolic simulation, 97
- symmetric coupling fault, 270
- symmetrical quantization, 357
- synchronous circuit, 212
- synchronous interference, 360
- syndrome, 604
- syndrome polynomial, 617
- syndrome testing, 513
- Synopsys, 171
- synthesis, 84
- system, 259, 595
- system clock, 523
- system clock phase, 235, 236
- system logic, 552
- system test, 48
- system voltmeter, 587
- system-on-a-chip, 15, 386, 575, 605, 611, 613

- t-diagnosability, 610
- Tafertshofer, 167, 203
- TAM, 608
- tap coefficient, 504
- TAP controller, 555
- TAP controller power-up reset, 557
- TAP controller timing, 557
- TBIC, 581
- TC, 36
- TCK, 553, 566, 580
- TDANPSF1G test, 291
- TDI, 553, 580
- TDO, 553, 580
- TDR, 299
- TDSNPSF1G test, 291
- technological efficiency, 35, 38
- technology-dependent fault, 60
- TEGAS, 109
- TEGUS, 203
- temperature, 260
- termination resistor, 586
- test access mechanism, 608
- test bus interface circuit, 580
- test complexity, 13
- test controller, 496
- test cube, 180
- test description language, 28
- test economics, 35
- test escape, 456
- test generation algebra, 159
- test generation complexity, 166
- test generation system, 204
- test head, 24, 26, 29
- test invalidation, 422
- test invalidation problem, 64, 542
- test length estimation, 505
- test pattern diffraction, 512
- test period, 337
- test plan, 22
- test point, 404, 491
- test point insertion, 528
- test program, 18, 22, 30
- test program generation system, 22
- test scheduling, 610
- test set length prediction, 146
- test sink, 608
- test site characterization, 20
- test source, 608
- test syndrome, 599
- test vectors, 18, 22
- test-collar, 606
- TEST-DETECT procedure, 116
- Test-Logic-Reset state, 567, 571
- test-pattern augmentation, 512
- test-pattern compaction, 512
- test-pattern generator, 496
- test-per-clock system, 521
- test-per-scan system, 521
- test-wrapper, 606
- testability analysis, 129
- testability index, 148
- testable path, 426
- testbench, 9, 92, 102
- tester load board, 452
- tester-independent program, 23
- testing, 8
- testing burnout, 14
- testing cost, 10, 35
- testing epoch, 516
- TF, 258, 266, 268
- Thadikaran, 626
- Thatte, 266
- THD, 358
- thermal noise, 380
- thermal verification, 614
- thermometer code, 327
- Thibeault, 456, 457
- third harmonic distortion, 356
- three-satisfiability, 164
- three-sigma range, 123
- three-state truth table, 97
- threshold test, 32
- threshold voltage, 14
- tiling method, 289
- time difference, 380
- time domain analog measurement, 398
- time domain reflectometer, 299
- time measurement unit, 379
- time slot, 105
- time to market, 35
- time wheel, 105
- time-frame, 216

- time-frame bound, 225
- time-frame expansion, 214, 215
- timed integrator, 336
- timing analysis, 434
- timing design of scan path, 479
- timing level, 91, 92
- Timoc, 624
- TLAPNPSF1G test, 290–292
- TLAPNPSF1T test, 291
- TLAPNPSF2T test, 291
- TLSNPSF1G test, 281, 291
- TLSNPSF1T test, 291, 292
- TLSNPSF2T test, 291
- TMS, 553, 580
- TMS1, 556
- TMS2, 556
- TMU, 379
- toggle coverage, 61
- tolerances, 386
- tone, 316
- tone frequency, 337
- tone pruning, 361
- top-down design, 595
- topological analysis, 129
- TOPS, 197
- total bus fault, 61
- total cost, 36, 39
- total harmonic distortion, 358
- TPG, 22, 496
- TRAN, 201, 203
- transfer map, 323
- transient fault, 259
- transient region, 99
- transistor fault, 70
- transistor trans-conductance, 387
- transition count, 514
- transition count test, 489, 514
- transition counter, 513, 519
- transition fault, 258, 268, 428
- transition tour, 87
- transition-delay fault, 61, 70
- transitive closure, 166
- transmission parameter, 316, 323
- transmission test, 317, 372
- transmit RAM, 371
- transparent test, 530, 539
- transport delay, 99
- tree, 67
- tree leaf, 158
- tri-state behavior, 167
- tri-state logic, 206
- trial vector, 240
- tristated leakage, 302
- tristated output leakage current, 302
- TRST, 553, 580
- true power, 348
- true process yield, 50
- true-value simulator, 84
- trunk signaling test, 359
- truth expression, 165
- Tsui, 624
- TSUNAMI, 204
- Tulloch, 623
- Turino, 624
- two-clock scan, 471
- two-coupling fault, 268
- two-group method, 289, 536
- two-satisfiability, 164
- type 1 LFSR, 503
- type 2 LFSR, 507
- Type-1 neighborhood, 272, 536
- Type-2 neighborhood, 272, 538
- Tyszer, 624
- Ulrich, 115, 628
- undersampling, 352
- unfactorable tones, 356
- unidirectional stuck-at fault, 300
- uniform sampling, 353
- uninitialized memory state, 215
- unique sensitization, 193
- unit test period, 316, 337, 341
- unit-delay simulator, 100
- universal rule for non-coherent sampling, 353
- unlinked fault, 278
- unnecessary hardware, 168
- unpowered open, 441
- unpowered testing, 578
- unrolling, 215
- untestable fault, 66, 70, 158
- UpdateDR signal, 559
- USE statement, 571
- user-defined instruction, 553
- USERCODE instruction, 563, 585
- UTP, 337, 341
- Uyar, 626
- validatable non-robust test, 426
- van de Goor, 253, 263, 266, 274, 278, 530, 534, 537, 626
- variable costs, 35, 36
- variable-clock delay testing, 432
- variance, 123
- VC, 36
- VCO, 337
- vector bus architecture, 318
- vector compaction, 9, 87
- vector dot product, 342, 347
- vector editor, 23
- verification, 8
- verification testing, 14, 17, 18, 500
- verification vectors, 87
- Verilog, 91, 490
- VHDL, 91, 490, 569
- VHDL package, 570
- VHDL package body, 570
- via resistance, 444
- vibration, 260
- Vinnakota, 385, 622
- virtual decision level, 325

- virtual edge, 325, 368
- virtual memory, 253
- virtual test, 28, 314
- VLASIC, 294
- VNR test, 426
- voltage bump, 301
- voltage bump test, 301
- voltage compliance limit, 587
- voltage drop device, 458
- voltage noise, 380
- voltage testing, 155
- voltage transmission, 591
- voltage-controlled oscillator, 337

- w, 262
- w0, 262
- w1, 262
- Wadsack, 68
- wafer prober, 27
- wafer sort test, 20, 30
- wafer yield, 45
- Waicukauski, 160, 624
- Walker, 628
- waveform correlation, 342
- waveform digitizer, 318, 322
- waveform generator, 27
- waveform information content, 355
- waveform synthesizer, 318, 320
- weak fault, 445, 448, 449
- weak fault table, 450
- weight select line, 511
- weight-sensitive fault, 536
- weighted pseudo-random pattern generation,
502, 510
- weighted random patterns, 160
- Weldon, 489, 509
- white noise, 316, 381
- Wilkes, 57
- Wilkins, 621
- Williams and Brown model, 53, 55
- Williams, M. J. Y., 467
- Williams, T. W., 53, 55, 467, 483, 506, 518,
622, 624
- wire-wrap board, 83
- write driver, 266
- write recovery fault, 531
- write recovery fault test, 304
- wrong chip insertion, 575
- WSF, 536
- Wunderlich, 161, 483

- X-list propagation, 610
- X-PATH-CHECK, 187

- Yarmolik, 623, 624
- yield, 19, 36, 45, 46, 53, 492
- yield loss, 6, 456, 493
- Yu, 117

- Z-domain, 397

- zero defects, 8, 439
- zero transmission level point, 368
- zero-delay simulator, 100
- zero-order-hold sampling, 355
- zero-width samples, 354
- zone number, 353
- Zorian, 623, 625